



THIN SHEET NUT-INSERT

MATERIAL : STAINLESS STEEL-A2

(AVK SERIES)

白鉄
AVK



SMALL FLANGE

DIMENSIONS (mm)

ITEM NO.	THREAD	A Max.	B ±0.40	C ±0.30	D ±0.1	Grip Range	Hole Size +0.15 / -0
SS-AK-832 (632)-80	#8-32(#6-32)	6.73	10.70	7.90	0.60	0.5 ~ 2.0	6.75
SS-AK-832 (632)-130	#8-32(#6-32)	6.73	11.90	7.90	0.60	2.0 ~ 3.3	6.75
SS-AK-1024 (1032)-130	#10-24(#10-32)	7.52	12.10	8.60	0.60	0.5 ~ 3.3	7.60
SS-AK-1024 (1032)-225	#10-24(#10-32)	7.52	14.90	8.60	0.60	3.3 ~ 5.7	7.60
SS-AK-420-165	#1/4-20	9.91	14.70	11.60	0.60	0.7 ~ 4.2	10.00
SS-AK-420-260	#1/4-20	9.91	17.30	11.60	0.80	4.2 ~ 6.6	10.00

LARGE FLANGE

INCH DIMENSIONS (mm)

ITEM NO.	THREAD	A Max.	B ±0.40	C ±0.30 *±0.64	D ±0.1	GRIP RANGE	Hole Size +0.15 / -0
SS-AL-832 (632)-80	#8-32(#6-32)	6.73	10.70	9.90	0.80	0.5 ~ 2.0	6.75
SS-AL-832 (632)-130	#8-32(#6-32)	6.73	11.90	9.90	0.80	2.0 ~ 3.3	6.75
SS-AL-1024 (1032)-130	#10-24(#10-32)	7.52	12.10	10.60	0.80	0.5 ~ 3.3	7.60
SS-AL-1024 (1032)-225	#10-24(#10-32)	7.52	14.90	10.50	0.80	3.3 ~ 5.7	7.60
SS-AL-420-165	#1/4-20	9.91	14.70	12.70	1.00	0.7 ~ 4.2	10.00
SS-AL-420-260	#1/4-20	9.91	17.30	12.70	1.00	4.2 ~ 6.6	10.00
SS-AL-518-150	#5/16-18	13.46	17.50	*17.40	1.00	0.7 ~ 3.8	13.50
SS-AL-518-312	#5/16-18	13.46	20.50	*17.40	1.00	3.8 ~ 7.9	13.50
SS-AL-616-150	#3/8-16	13.46	17.50	*17.40	1.00	0.7 ~ 3.8	13.50
SS-AL-616-312	#3/8-16	13.46	20.50	*17.40	1.00	3.8 ~ 7.9	13.50

有模具 →

